

steel pid



Professional Thermoblock
Aluminium + Inox



3
YEAR
WARRANTY
COFFEE GROUP

Stainless steel. Multidirectional 360°. Heat resistant.
Easy to clean.
Acero inox. Multidireccional 360°. Anticalórico. Fácil de limpiar.



Inox PROF wand
Tubo PROF inox



Electronic thermostat (adjustable)
Thermal stability $\pm 1,5^{\circ}\text{C}$ / Stand-by
Termostato electrónico (regulable)
Estabilidad térmica $\pm 1,5^{\circ}\text{C}$ / Stand-by



3 ways solenoid. Perfect dry doses. No leaking.
No over pressure.
Made of unleaded brass + stainless steel AISI316
Electroválvula 3 vías. Dosis secas. No gotea.
No sobrepresión.
Fabricado en latón sin plomo + inox AISI316



Tilted filter holder 10°. (PROF models).
Non slip grip handle. Ergonomic.
Portafiltro inclinado 10°. (PROF molido).
Zona antideslizante. Ergonómico.



Adjustable pressure valve (OPV). 8 to 15 bars.
(only ground model)
Válvula de presión regulable. 8 a 15 bars (sólo sistema molido)



Professional steam/water tap. Closure with viton gasket.
Grifo profesional vapor/agua. Cierre con junta vitón.



Aluminium tamper included. (Ground models)
Prensacafé aluminio incluido. (Modelos molido)

Inox and large cupwarmer (315x270mm)
Amplio escaudatazas inox.

INOX 100%.

Brass professional group (Ø60mm).
Grupo latón profesional (Ø60mm).

Blue leds and metallic switches.
Leds azules. Interruptores metálicos.

Removable water tank.
Depósito de agua extraíble.

Visual water level.
Nivel agua visual.

Powerful steam/hot water.
Potente vapor/agua caliente.

Improvements over Steel

Mejoras sobre Steel



steel duo (2 GROUPS)

DUO



BLACK

DUO PID



BLACK&WOOD



WHITE&WOOD



FULL INOX&WOOD

All DUO models in two systems
Todos los modelos DUO en dos sistemas

Only Pod
Sólo monodosis



Versatile
Versátil



steel series

• PM = Removable arm Porta móvil • PF = Fixed arm Porta fijo

Model / Modelo	i-steel (PM)	uno (PM)	uno (PF)	duo (PM)	duo (PF)	trio (PM)	trio (PF)
Length/height/depth (mm) Largo/alto/profundo(mm)	410x440 x460	270x360 x315	270x360 x315	270x360 x315	270x360 x315	480x360 x315	480x360 x315
Water tank (liters) Depósito agua (litros)	2	2	2	2	2	2+2	2+2
Weight Kg Peso Kg.	16	12	11	15	15	21	21
Power (W) Potencia (W)	1300	1052	1052	2068	2068	3112	3112
Coffee thermostats Termostatos café	Electronic 98°	Electronic 98°	Electronic 98°	Electronic 98°	Electronic 98°	Electronic 98°	Electronic 98°
Safety thermostat / OPV (Over Pressure Valve) Termostato seguridad / Válvula presión regulable	X	X	X	X	X	X	X
Brass filter holder Portafiltro latón	(Ø 60 mm)	(Ø 60 mm)	X	(Ø 60 mm)	X	(Ø 60 mm)	X
Coffee solenoid (no drip) Electroválvula café (antigoteo)	X	X	X	X	X	X	X
Independent steam group / water (with solenoid) Grupo vapor independiente / Agua (con electroválvula)				X	X	X	X
Coffee Tamper (rem. arm) / Spoon (7gr) Prensa Café (porta móvil) / Cuchara (7gr)	X	X		X		X	

50

Voltaje 230V/120V, Pump Pressure 20 BAR, Steam thermostat 140°, Steam pipe protector. Cappuccino/hot water pipe: In all models
 Voltaje 230V/120V, Pump Pressure 20 BAR, Termostato vapor 140°. Protector tubo vapor. Tubo cappuccino/agua caliente: en todos los modelos